

BLUEline

AdBlue® (max. density: 1.6 g/cm³)

BLUEline IBCs are equipped with additional openings or withdrawal systems, amongst others, also for AdBlue®.

- Optionally with integrated CDS or Micromatic withdrawal system
- Optionally without integrated valve
- With PMDS lid (Pressure Management Discharge System) emptying possible without opening the lid
- UN version possible



Product	Inner container	Pallets						Valve			Lid	
	Volume Litre	Wood L x W x H	Weight kg	Plastic L x W x H	Weight kg	Combi L x W x H	Weight kg	with-out	DN 50	DN 80	DN 150	DN 225
BLUEline (AdBlue®)	300	–	–	600 x 800 x 1000	24	–	–	●	●	–	●	–
	600	–	–	1200 x 800 x 1013	48	–	–	●	●	●	●	●
	1000	1200 x 1000 x 1164	63	1200 x 1000 x 1163	58	1200 x 1000 x 1135	60	●	●	●	●	●



CDS withdrawal system
With dip tube



Flange
With tap S 56 x 4



Lid
PMDS



Micromatic
Available for 300 l, 600 l and 1000 l IBCs

MODULAR SPECIALISTS

1000 litre

Plastic lid
150 mm, 225 mm, 400 mm

Steel cross-bracing

Inner container made from
UV stabilising HDPE

Fill level scale



Individualisation by
means of stickers
possible

Steel traverses on the pallet

Plastic pallet
Combi pallet
Wooden pallet

Steel label sign
722 mm x 390 mm (2816 cm²)
Optional:
Back side
722 mm x 350 mm (2527 cm²)
Outer side:
605 mm x 350 mm (2118 cm²)

Valve: DN 50, DN 80

Plastic corner protector
with UN-IBC



Plastic skid pallet

12/10 (1200 x 1000 mm)
also available as **frame pallet**
12/08 (1200 x 800 mm)



Combi pallet with skids

12/10 (1200 x 1000 mm)



Wooden skid pallet (IPPC)

12/10 (1200 x 1000 mm)
also available as **flat pallet**
12/08 (1200 x 800 mm)